

SUPRA 20W-50

PREMIUM PETROL ENGINE OIL

BULWARK SUPRA oils are mainstream multi-grade mineral motor oils suitable for use in engines of passenger cars, light commercial trucks and vans including turbocharged engines. The product is manufactured using high quality mineral base stocks and advanced technology additive packages to provide the best anti-wear protection and all-round superior performance.

BULWARK SUPRA 20W-50 oil is recommended for use during all-season operations in gasoline engines of cars from Japanese, American and Korean manufacturers, where API SL performance is required.

PERFORMANCE LEVEL

- API SL/CF

KEY BENEFITS

- High antioxidation and better dispersant properties
- Low oil consumption.
- Minimizes wear and noise level (especially in older and worn engines) during extreme operational conditions.
- Excellent protection against corrosion.

TYPICAL CHARACTERISTICS

Properties	Test Methods	20W-50
Density @ 29.5°C, Kg/m ³	ASTM D4052	0.885
Kinematic Viscosity @ 100°C cSt	ASTM D7042	18.50
Viscosity Index	ASTM D2270	127
Cold Cranking Viscosity, mPa-s	ASTM D5293	8350 at -15°C
Borderline Pumping Viscosity, mPa-s	ASTM D4684	33,120 at -20°C
Sulphated Ash, %	ASTM D874	1.05
Flash Point, COC, °C	ASTM D92	248
Foam Stability	ASTM D892	
Seq I		0/0
Seq II		0/0
Seq III		0/0
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896B	7.45

PS: The above information is typical data and an indication based on current production. It does not constitute a specification.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Bulwark International UK Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

Bulwark International UK Ltd, 34 Woodland Road, Sawston, CB22 3DU, United Kingdom. info@bulwarkauto.co.uk