

BRAKE FLUID DOT 4

BRAKE & CLUTCH FLUID

BULWARK BRAKE FLUID DOT 4 is a premium quality glycol ether & borate ester-based fluid with advanced corrosion inhibitors recommended for use in brake systems specifically for modern braking systems with electronic control systems such combined with ABS, ASC and ESP/DSC. Its Low viscosity and higher boiling point provide better braking efficiency.

DIRECTIONS TO USE

The brake fluid is hygroscopic and must be stored in tightly sealed containers. After removal of brake fluid, the containers must be closed immediately. **BULWARK BRAKEFLUID DOT 4** has a shelf life of at least three years when stored in original closed, airtight containers at temperatures of maximum 40 °C.

PERFORMANCE LEVEL

- SAE J 1704, 1703
- FMVSS 116 DOT 4

KEY BENEFITS

- Extremely low viscosity at low temperatures
- Product contains multi-metal corrosion inhibitors which gives engine excellent protection for ferrous & non-ferrous metals.
- Compatible with other DOT 4 brake fluids.
- Exceptional lubricity performance and thermal stability provides extended service life.
- Superior elastomer compatibility.

TYPICAL CHARACTERISTICS

Properties	Test Methods	DOT 4
Appearance	Visual	Clear & Bright
Density @ 29.5°C	ASTM D 4052	1.07
Viscosity @ 100°C, cSt	ASTM D 445	2.0
Viscosity @ 40°C, cSt	ASTM D 445	1100
WERBP, °C	ASTM D 1120	160
Boiling Point, °C	ASTM D 1120	265
Flash Point, °C	ASTM D 92	124

PS: The above information is typical data and an indication based on current production. It does not constitute a specification.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Bulwark International UK Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

Bulwark International UK Ltd, 34 Woodland Road, Sawston, CB22 3DU, United Kingdom. info@bulwarkauto.co.uk