

ITURBINE TDG 32

PREMIUM TURBINE OIL

BULWARK ITURBINE TDG OILS are high quality conventional turbine oils that combine excellent aging stability at higher operating temperatures, excellent air release, quick water separation and excellent corrosion inhibition. These oils are free from Zinc, chlorine, PCB and PCT.

BULWARK ITURBINE TDG 32 OIL can be used on steam and gas turbines and several other applications including circulation & bearing lubrication system or hydraulics (with Zinc & Zinc-Free) or light & medium duty Industrial gear & Bearing Oils operating under severe conditions.

Note: These turbine oils are not suitable to use if the OEM recommends use of turbine oils with extreme pressure (EP) and anti-wear properties. Please send us your enquiry with OEM specifications for such high-performance Turbine oils, which are available with BULWARK only on a subject to enquiry basis.

PERFORMANCE LEVEL

- DIN 51515-1 TD
- SIEMENS TLV 901304

KEY BENEFITS

- Multi-use product and provides excellent aging stability
- Excellent air release and quick water separation & corrosion inhibition
- Zinc free product.

TYPICAL CHARACTERISTICS

Properties	Test Methods	32
Density at 15°C, kg/m3	ASTM D4052	0.878
Viscosity at 40 °C, cSt	ASTM D445	32.07
Viscosity at 100°C, cSt	ASTM D445	5.37
Pour point, °C	ASTM D97	-24
Flash point COC, °C	ASTM D92	228
Viscosity Index	ASTM D2270	100
Air release at 50°C, Minute	ASTM D3427	2
Oxidation (TOST)	ASTM D943	>2200
Form Tendency/Form Stability	ASTM D892	
Seg I		0/0
Seg II		0/0
Seg III		0/0
Water Separability at 54 °C	ASTM D1401	
Time for Separation, min		8
Volume of layer (oil - water - emulsion), ml		42-38-0
Copper Corrosion (3 hrs at 100 °C)	ASTM D130	1b

PS: The above information is typical data and an indication based on current production. It does not constitute a specification.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Bulwark International UK Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

Bulwark International UK Ltd, 34 Woodland Road, Sawston, CB22 3DU, United Kingdom. info@bulwarkauto.co.uk