

iGEAR CLP 150

PREMIUM INDUSTRIAL GEAR OIL

BULWARK iGEAR CLP OILS are high quality gear lubricants for heavy loaded industrial gearboxes and bearings. These oils are manufactured using carefully selected high viscosity Index base oils with advanced sulphur-phosphorus extreme pressure additives. Its optimal ratio of EP properties and anti-friction protection capabilities allow using these oils effectively in various components and gear units of industrial equipment.

BULWARK iGEAR CLP 150 OIL is recommended for industrial gearboxes and units with steel gears, where EP oils are required. The applications also include bearings, wheel, worm and screw gears in different industrial equipment, as well as oil circulation and mist and splash lubricating systems.

PERFORMANCE LEVEL

- DIN 51517-3 CLP
- ANSI/AGMA 9005-E02 (EP)
- ISO 12925-1 CKD
- US Steel 224

KEY BENEFITS

- Excellent EP properties and anti-friction capabilities allow using these oils on various applications and components of industrial equipment
- Provides protection to wide range of gear boxes industrial equipment.
- The formula provides excellent low temperature fluidity and exceptional resistance to degradation at high temperatures.
- Prevents welding, scuffing and galling of the gear teeth at their contact points.
- Provide exceptional oil life and deposit control and resistance to thermal/oxidative and chemical degradation.

TYPICAL CHARACTERISTICS

Properties	Test Methods	150
Density at 29.5 kg/m ³	ASTM D4052	0.891
Kinematic viscosity at 40°C, cSt	ASTM D445	146.5
Kinematic viscosity at 100°C, cSt	ASTM D445	14.43
Viscosity Index	ASTM D2270	96
Flash Point, COC, °C	ASTM D92	246
Pour Point, °C	ASTM D97	-24
Form Tendency/ Form Stability	ASTM D892	
Seg I		0/0
Seg II		0/0
Seg III		0/0

PS: The above information is typical data and an indication based on current production. It does not constitute a specification.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Bulwark International UK Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

Bulwark International UK Ltd, 34 Woodland Road, Sawston, CB22 3DU, United Kingdom. info@bulwarkauto.co.uk